

FEATURES

- Low PIM: ≤ -160 dBc
- Low VSWR: $\leq 1.20:1$ up to 3 GHz
- Non-tarnish White Bronze (Tri-Metal) plating



Similar in mechanical design to the 7-16 DIN interface, the compact 4.1-9.5 Type DIN offers improved performance over the N-Type interface for wireless infrastructure applications.

4.1-9.5 (Mini) DIN to 4.1-9.5 (Mini) DIN



4.1-9.5 Male to 4.1-9.5 Female
RFD-4195-1950

4.1-9.5 (Mini) DIN to N



4.1-9.5 Male to N Female
RFN-1046-4

4.1-9.5 (Mini) DIN to 7-16 DIN



4.1-9.5 Male to 7-16 Female
RFD-1681-4



4.1-9.5 Female to 4.1-9.5 Male
RFD-4195-1952



4.1-9.5 Male to N Male
RFN-1045-4



4.1-9.5 Male to 7-16 Male
RFD-1682-4



4.1-9.5 Female to N Female
RFN-1047-4



4.1-9.5 Female to 7-16 Female
RFD-1683-4



4.1-9.5 Female to N Male
RFN-1048-4



4.1-9.5 Female to 7-16 Male
RFD-1684-4

SPECIFICATIONS

Impedance.....	50 Ohms
Frequency Range	DC to 7.5 GHz
VSWR.....	< 1.20:1 up to 3 GHz
Intermodulation, 3rd Order IM	≤ -160 dBc @ 2 x43 dBm
Number of Matings	500
Operating Temperature.....	-55° C to + 165° C

Note: Specifications subject to change without notice

RF Industries

(NASDAQ: RFIIL)

7610 Miramar Road
San Diego, CA 92126
(800) 233-1728
(858) 549-6340
Fax: (858) 549-6345
rfi@rfindustries.com
www.rfindustries.com