

Features

Wide Frequency Band DC-6GHz

2G/3G/4G/5G/LTE Coverage

Low VSWR

Widely used for In-building Solutions

In-line, bi-directional attenuators for managing signal power levels. Available in various attenuation values, connectors, frequencies and power levels. Applications include Distributed Antenna Systems (DAS), test equipment and electrical circuits where power levels need to be reduced.



GENERAL SPECIFICATIONS

Frequency Range	DC-6GHz
Impedance.....	50Ω
Power Rating.....	5 (average)
VSWR	≤1.25
Temperature Range.....	-30° C to +65° C
Connector Type.....	4.3-10 male to 4.3-10 female
Weight.....	0.26 (lbs)

Model Number	Attenuation (dB)	Accuracy (dB)
RF-ATN-43MF-5W3	3dB	±0.5
RF-ATN-43MF-5W4	4dB	±0.5
RF-ATN-43MF-5W5	5dB	±0.5
RF-ATN-43MF-5W6	6dB	±0.5
RF-ATN-43MF-5W7	7dB	±0.6
RF-ATN-43MF-5W8	8dB	±0.6
RF-ATN-43MF-5W9	9dB	±0.6
RF-ATN-43MF-5W10	10dB	±0.8
RF-ATN-43MF-5W11	11dB	±0.8
RF-ATN-43MF-5W12	12dB	±0.8
RF-ATN-43MF-5W13	13dB	±0.8

