


PART NO.

RFD-43M-NF

REV	DESCRIPTION	DWN	DATE	APPROVED
-	ENGINEERING RELEASE	CZS	06/22/15	JDMc

SPECIFICATIONS:

IMPEDANCE: 50 Ohms

FREQUENCY RANGE: 0-6 GHz

VSWR: ≤ 1.15 3rd ORDER IM: < -160 dBc @ 1900 MHz

DIELECTRIC WITHSTANDING VOLTAGE: 2000V/AC

INSULATION RESISTANCE: 1000M Ω OPERATING TEMPERATURE: -40° to $+155^{\circ}$

#	DESCRIPTION	QTY	MATERIAL	FINISH
7	RETAINING RING	1	BRASS	WHITE BRONZE
6	COUPLING NUT	1	BRASS	WHITE BRONZE
5	GASKET	1	S.I. RUBBER	---
4	GROUND RING	1	BeCu	WHITE BRONZE
3	INSULATOR	1	PTFE	---
2	CONTACT	1	BeCu	SILVER
1	BODY	1	BRASS	WHITE BRONZE

CUSTOMER
OUTLINE DRAWINGALL DIMENSIONS
ARE REFERENCE ONLYUNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
AND [MILLIMETERS]DRAWN
C. ZUNIGA 06/22/15
CHECKEDORJ DRAWN
C. ZUNIGA 06/22/15**RoHS
COMPLIANT**PROPRIETARY AND CONFIDENTIAL
THIS DRAWING CONTAINS
INFORMATION PROPRIETARY TO
RF INDUSTRIES. ANY
UNAUTHORIZED USE OF THIS
DRAWING IS EXPRESSLY
PROHIBITED WITHOUT WRITTEN
PERMISSION FROM RF
INDUSTRIES. ANY VIOLATION IS
PUNISHABLE UNDER U.S.
COPYRIGHT LAWS.

RFconnectors
DIVISION OF RF INDUSTRIES, LTD.

7610 MIRAMAR RD.
SAN DIEGO, CA 92126
(858) 549-6340
(858) 549-6345 FAX

**4.3/10 MALE TO N FEMALE
ADAPTER**

SIZE	CABLE GROUP	DWG NO.	REV
A	N/A	RFD-43M-NF	—
SCALE:	ENGINEERING ID:	SHEET 1 OF 1	
NTS	000000		