



THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES.
 ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED
 WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES.
 ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

ALL DIMENSIONS ARE REFERENCE ONLY

PART NO.

RSA-3400

REV	DESCRIPTION	OWN	DATE	APPROVED
-	ENGINEERING RELEASE	CZS	10/01/02	JUMc



SPECIFICATIONS:

IMPEDANCE: 50 Ohms
 WORKING VOLTAGE: 335 V rms Max. @ Sea Level
 INSULATION RESISTANCE: 5k MOhms min.
 TEMPERATURE RANGE: -55°C TO 85°C

1	HOUSING	1	BRASS	NICKEL, 100μ"
2	BODY (PLUG)	1	BRASS	NICKEL, 100μ"
3	BODY (JACK)	1	BRASS	NICKEL, 100μ"
4	CONTACT	1	BeCu	GOLD, 3μ"
5	PIN	1	BRASS	GOLD, 3μ"
6	INSULATOR	1	PTFE	---
7	INSULATOR	2	PTFE	---
8	RETAINING RING	1	BeCu	NICKEL, 100μ"
9	GASKET	1	RUBBER	---
10	END CAP	1	BRASS	NICKEL, 100μ"
11				
12				
13				
14				
#	DESCRIPTION	QTY	MATERIAL	FINISH

000712

DRAWN	C. ZUNIGA	10/01/02
CHECKED	<i>[Signature]</i>	10-1-02
ORJ DRAWN	C. ZUNIGA	10/01/02
APPROVALS	DATE	

UNLESS OTHERWISE SPECIFIED:

1. REMOVE ALL BURRS
2. BREAK ALL CORNERS & EDGES .005 R. MAX.
3. CHAMFER 1ST & LAST THREADS 45°
4. SURFACE ROUGHNESS 63 FINISH MIL-STD-10
5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .002 T.I.R.
6. ALL DIMENSIONS ARE AFTER PLATING.

DIMENSIONS ARE IN INCHES AND [MILLIMETERS]
 UNLESS OTHERWISE NOTED TOLERANCES ARE:
 DECIMALS DIAMETER
 .xxx±.003 [.08] .xxx±.001 [.03]
 .xx±.005 [.13] .xx±.003 [.08]

RFconnectors
 DIVISION OF RF INDUSTRIES, LTD.

7610 MIRAMAR RD
 SAN DIEGO, CA 92126
 (858) 549-6340
 (858) 549-6345 FAX

SMA PLUG TO DOUBLE JACK

T ADAPTER

SIZE	CABLE GROUP	DWG NO.	REV
A	N/A	RSA-3400	-
SCALE: NTS		CAD FILE OUTLINE	SHEET 1 OF 1